

New Zealand CIF price 1 6T optical module 1 6T



Overview

Each module integrates eight electrical and eight optical channels operating at 212.5 Gbps PAM4 per lane for an aggregate data rate of 1.6T. With integrated DSP and silicon photonics (SiPh) technology, it provides excellent signal integrity and reach up to 500m. It concludes with the FS 1.6T OSFP-XD DR8 PAM4 Optical Transceiver Module (1311nm MTP/MPO-16 SMF 2km). Excellent quality is the foundation of FiberMall's survival and development. Our operation team are experts with many years' experience in the optical communication industry. 6T/800G InfiniBand XDR solutions, which combine transceivers with cables. 6T 2xDR4 and 2xFR4 OSFP224 transceivers in IHS and RHS versions, 800G DR4 OSFP224 transceivers in RHS version, and original NVIDIA transceivers (MMS4A00-XM, MMS4A20-XM800). Amphenol's 200G/lane optical modules support DR4, FR4, 2xDR4, 2xFR4, AOC, and breakout AOC configurations with LC or MPO ports, ideal for 800G/1.6T. Fully compliant with OSFP MSA, IEEE 802.3. Comprising five flagship platforms, Centenario, Jesko, Portofino, Gemera, and Cygnus, Broadcom's DSP PAM-4 portfolio covers 100G, 400G, 800G, and 1.6T.

Article Content

1.6T/800G InfiniBand XDR Transceivers/DACs In Stock NADDOD

NADDOD offers 1.6T/800G InfiniBand XDR solutions, which combine transceivers with cables. The transceiver portfolio includes 1.6T 2xDR4 and 2xFR4 OSFP224 transceivers in IHS and RHS ...

1.6T OSFP-XD DR8 MPO-16 Optical Transceiver

FiberMall OSFP-XD-1.6T DR8 transceiver is a high-performance optical module ...

1.6T OSFP-XD DR8 MPO-16 Optical Transceiver | FiberMall

FiberMall OSFP-XD-1.6T DR8 transceiver is a high-performance optical module with a maximum transmission distance of 2 km, suitable for high-bandwidth requirements.

1.6T OSFP224 Optical Transceiver Modules | AscentOptics

OSFP224 1.6T transceivers support CMIS 5.0+, with DR8, DR8+, and 2xFR4 interfaces. Integrated optical engines deliver high performance and efficiency - AscentOptics.

1600G OSFP1600 2xDR4 500M 1.6T Optical Transceiver

The 1600G OSFP1600 2xDR4 Transceiver is designed to transmit and receive serial optical data links up to 212.5 Gbps data rate (per channel) by PAM4 modulation format over single-mode fiber. It is a ...

1.6T 2xFR4 OSFP PAM4 Optical Transceiver

Optical Transceiver Jabil 1.6T 2xFR4 OSFP PAM4 Optical Transceiver is a small form-factor, high speed, and low power consumption product targeted for use in optical interconnects for data ...

100G to 1.6T Optical Module PHY Product Selection Guide

Broadcom's Active Copper PHY portfolio enables DAC cable providers to build very low insertion-loss profile, ultra-low latency, ultra-low power cables for 100G/400G/800G/1.6T hyperscale/AI networks ...

1.6T 2xDR4 TRO OSFP Transceiver Module | Lumentum

Each module integrates eight electrical and eight optical channels operating at 212.5 Gbps PAM4 per lane for an aggregate data rate of 1.6 Tbps. With integrated DSP and silicon photonics (SiPh) ...

1.6T Transceivers Explained: Advantages, Types & FS Solution

This article explains how this new 1.6T rate emerged, what the technical principles and key features of 1.6T optical modules are, the major module types involved, and the application ...

1.6T OSFP Transceivers | Optical Transceivers | Amphenol

Amphenol's 1.6T OSFP transceiver delivers 200G per lane to support advanced 800G and 1.6T Ethernet applications, enabling high-speed, high-density optical connectivity.

1.6T OSFP DR8 LPO-1.6T high-speed optical module

The MTRO-D5F8CL is designed to operate in switch and router applications supporting OSFP MSA compliant traffic for up to 500m links.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://budowasilesia.pl>

Email: contact@budowasilesia.pl

Phone: +48 537 192 846

Address: ul. Chorzowska 45, 40-001 Katowice, Silesian Voivodeship, Poland

This document is for informational purposes only. Specifications subject to change without notice.

